



AUDIO BOOM ALARM

Audible Boom Alarm warns operator to check boom position as the vehicle brakes are released. (Only if the boom was moved)

Features:

- 12-24 volt vehicle power
- Simplified Wiring
- Mutil-Language
- Custom Warning Phrase
- Nuisance operation is eliminated by only warning following a valid boom operation
- LED indicator illuminated during message delivery
- Tamper resistant



Complete System Part #: N54-0051



The Ultimate protection for your boom truck operators. Eliminate high maintenance / low reliability boom position feedback sensors System "Speaks" Audible reminder phrase as the operator leaves.



3.5" Weatherproof Industrial Design



LED Visible Indicator During Warning



AUDIO BOOM ALARM

Product Details

Wiring List:

- Cond 1: Vehicle Power (+24 key)
- Cond 2: Vehicle Gnd (0v)
- Cond 3: Boom Active (latched internally) (+24 when boom active)
- Cond 4: Brake Release (+24 when brakes are released)



Specifications

Damage due to an improperly positioned boom with low U/G clearance is costly. Boom Alarm addresses this issue by producing an audible message when the brakes are released. Nuisance warnings are eliminated by only issuing the customized "Warning Message" if the boom had been used that stop.

- Power: 20 – 28 vdc
- Size: 8.25" x 4.25" x 2.50"
- Speaker: 5 watt (Heavy Equipment duty)
- Indicator: Amber LED
- Body: Machined PVC (non-corroding)
- Temperature: -20 to +50 deg C
- Message: Pre-recorded (up to 8 variations)
- Volume: Adjustable (internal)

Audible messages can be pre-recorded to suit specific requirements and accommodate various languages. Consult factory for range of options.

Minewise Technology Ltd.

727 Lorne St. | Sudbury | Ontario | P3C 4R5 | Canada
Phone: (705) 674-3332 | Fax: (705) 674-2221
www.minewise.com | sales@minewise.com